

定格総荷重表

種類および型式		BM1000G クローラクレーン型 ジブ (補助シーブ装着)															単位: t		
ジブの長さ		13.8m	16.9m	19.9m	23.0m	26.0m	29.1m	32.1m	35.2m	38.2m	41.2m	44.3m	47.3m	50.4m	53.4m	56.5m	59.5m	ジブの長さ	
作業半徑 (m)	4.3	89.2	86.7	4.8m / 77.2															4.3
	5.0	73.2	73.2	72.7	5.4m / 69.2	5.9m / 60.7													5.0
	6.0	60.7	60.7	60.7	60.7	60.2	6.4m / 56.0												6.0
	7.0	50.5	50.3	50.2	50.1	50.0	50.0	44.0	7.5m / 44.2										7.0
	8.0	41.6	41.4	41.3	41.2	41.1	41.0	41.0	40.9	40.5	8.5m / 36.7								8.0
	9.0	35.2	35.1	34.9	34.8	34.7	34.7	34.6	34.5	34.4	34.3	9.1m / 33.8	9.6m / 31.0						9.0
	10.0	30.5	30.3	30.2	30.1	30.0	29.9	29.8	29.7	29.6	29.5	29.4	29.3	10.1m / 24.2	10.7m / 24.2	11.2m / 20.8	11.7m / 19.3		10.0
	12.0	21.2	23.7	23.5	23.4	23.3	23.2	23.2	23.0	22.9	22.8	22.7	22.6	22.5	22.4	18.7	18.6		12.0
	14.0	13.2m / 17.9	19.3	19.1	19.0	18.9	18.8	18.7	18.6	18.4	18.4	18.2	18.1	18.1	17.9	17.8	17.2		14.0
	16.0		15.8m / 14.1	16.0	15.9	15.7	15.7	15.6	15.4	15.3	15.2	15.1	14.9	14.9	14.7	14.6	14.2		16.0
	18.0			12.8	13.5	13.4	13.3	13.2	13.0	12.9	12.9	12.7	12.6	12.5	12.4	12.2	12.1		18.0
	20.0			18.5m / 11.7	11.7	11.6	11.5	11.4	11.2	11.1	11.0	10.8	10.7	10.7	10.5	10.4	10.2		20.0
	22.0				21.1m / 10.3	10.1	10.0	9.9	9.7	9.6	9.5	9.4	9.2	9.2	9.0	8.9	8.8		22.0
	24.0					23.8m / 9.0	8.8	8.7	8.5	8.4	8.3	8.2	8.0	8.0	7.8	7.7	7.6		24.0
	26.0						7.9	7.7	7.5	7.4	7.3	7.2	7.0	7.0	6.8	6.7	6.5		26.0
	28.0						26.4m / 7.4	6.9	6.7	6.6	6.5	6.3	6.2	6.1	6.0	5.8	5.7		28.0
	30.0							29.0m / 6.5	6.0	5.9	5.8	5.6	5.5	5.4	5.2	5.1	5.0		30.0
	32.0								31.7m / 5.5	5.3	5.2	5.0	4.8	4.8	4.6	4.5	4.3		32.0
	34.0									4.7	4.6	4.4	4.3	4.2	4.0	3.9	3.8		34.0
	36.0									34.3m / 4.7	4.1	4.0	3.8	3.7	3.6	3.4	3.3		36.0
	38.0										37.0m / 3.9	3.5	3.4	3.3	3.1	3.0	2.9		38.0
40.0											39.6m / 3.2	3.0	2.9	2.8	2.6	2.5		40.0	
42.0												2.7	2.6	2.4	2.2			42.0	
44.0													42.2m / 2.7	2.3				44.0	
46.0																		46.0	
最大ジブ角度	78°	80°	80°	80°	80°	80°	80°	80°	80°	80°	80°	80°	80°	80°	80°	80°		最大ジブ角度	
最小ジブ角度	30°	30°	30°	30°	30°	30°	30°	30°	30°	30°	30°	30°	30°	36°	44°	47°	52°	最小ジブ角度	
標準掛数	8	7	7	6	5	5	4	4	4	3	3	3	2	2	2	2		標準掛数	

内の定格総荷重は強度域である。