

定格総荷重表

種類および型式		7200G クローラクレーン型 (カウンタウェイト上部8枚, 下部2枚) ジブ(補助シーブ装着)/補助シーブに13.5tボールフック装着															単位:t	
ジブの長さ	18.3m	21.3m	24.4m	27.4m	30.5m	33.5m	36.6m	39.6m	42.7m	45.7m	48.8m	51.8m	54.9m	57.9m	61.0m	64.0m	ジブの長さ	
作業半徑(m)	5.0	198.2	5.5m /173.2														5.0	
	6.0	187.8	173.2	148.2	6.6m /148.2												6.0	
	7.0	162.1	161.7	148.2	148.2	7.1m /123.2	7.6m /123.2										7.0	
	8.0	142.5	142.1	141.7	141.5	123.2	123.2	8.2m /98.2	8.7m /98.2								8.0	
	9.0	127.0	126.6	126.2	126.0	123.2	121.3	98.2	98.2	9.2m /97.0	9.7m /85.7						9.0	
	10.0	114.5	114.0	113.7	113.4	113.0	112.8	98.2	98.2	94.9	85.7	10.3m /73.2	10.8m /73.2	11.3m /69.8	11.9m /60.7		10.0	
	12.0	88.8	88.6	88.4	88.2	88.0	87.8	87.8	87.6	87.4	83.5	73.2	73.2	68.7	60.7	12.4m /59.2	12.9m /48.2	12.0
	14.0	71.2	70.9	70.7	70.5	70.3	70.1	70.0	69.8	69.6	69.5	69.3	68.9	64.8	60.1	56.5	48.2	14.0
	16.0	59.2	58.9	58.6	58.4	58.2	58.0	57.9	57.6	57.4	57.3	57.1	56.9	56.6	56.5	53.1	48.2	16.0
	18.0	17.4m /51.1	50.1	49.8	49.6	49.4	49.1	49.0	48.7	48.5	48.4	48.2	48.0	47.7	47.7	47.4	46.3	18.0
	20.0		43.5	43.2	42.9	42.7	42.4	42.3	42.0	41.8	41.6	41.4	41.2	41.0	40.9	40.6	40.5	20.0
	22.0		20.1m /43.3	37.9	37.7	37.4	37.2	37.0	36.7	36.5	36.3	36.1	35.9	35.7	35.5	35.3	35.2	22.0
	24.0			22.7m /36.4	33.5	33.2	32.9	32.8	32.5	32.2	32.1	31.8	31.6	31.4	31.2	31.0	30.9	24.0
	26.0				25.4m /31.1	29.7	29.4	29.3	29.0	28.7	28.5	28.3	28.1	27.8	27.7	27.4	27.3	26.0
	28.0					26.8	26.5	26.4	26.0	25.8	25.6	25.4	25.1	24.9	24.7	24.5	24.4	28.0
	30.0						24.1	23.9	23.6	23.3	23.1	22.9	22.6	22.4	22.2	21.9	21.8	30.0
	32.0							30.6m /23.4	21.8	21.4	21.2	21.0	20.7	20.5	20.2	20.0	19.8	32.0
	34.0								33.2m /20.6	19.6	19.3	19.1	18.9	18.6	18.4	18.1	17.9	34.0
	36.0									35.9m /18.1	17.7	17.5	17.2	17.0	16.7	16.5	16.3	36.0
	38.0										16.3	16.1	15.8	15.5	15.3	15.1	14.8	38.0
40.0										36.6m /16.0	14.8	14.5	14.3	14.0	13.8	13.5	40.0	
42.0											41.2m /14.1	13.4	13.1	12.8	12.6	12.4	42.0	
44.0												43.8m /12.5	12.1	11.8	11.6	11.3	44.0	
46.0													11.2	10.9	10.6	10.4	46.0	
48.0													46.5m /11.0	10.1	9.8	9.5	48.0	
50.0														49.1m /9.7	9.0	8.8	50.0	
52.0															51.8m /8.4	8.1	7.9	52.0
54.0																7.4	7.2	54.0
56.0																54.4m /7.3	6.6	56.0
58.0																	57.0m /6.4	58.0
最大ジブ角度	80°	80°	80°	80°	80°	80°	80°	80°	80°	80°	80°	80°	80°	80°	80°	80°	最大ジブ角度	
最小ジブ角度	30°	30°	30°	30°	30°	30°	30°	30°	30°	30°	30°	30°	30°	30°	30°	30°	最小ジブ角度	
標準掛数	16	14	12	12	10	10	8	8	8	7	6	6	6	5	5	4	標準掛数	

